LITHIUM-POLYMER RECHARGEABLE

INTRINSICALLY SAFE DUAL-LIGHT HEADLAMP

XPR-5554G

NIGHTSTICK®
Life Depends on Light™

DUAL LIGHT TECHNOLOGY

IP-67 DUST/WATER PROOF

ATEX ZONE 0 IECEx

CLASS I DIV 1

UP TO 16 HOURS OF RUNTIME IN LOW MODE

MULTI-POSITION TILT-HEAD DESIGN

Includes NS-HMC9 and Stainless Steel Clip Back Plate for zero band application.

Magnetic Waterproof USB Coupling
Never worry about water getting inside your headlamp.

Dual-Light Technology, focused spotlight and area floodlight at the same time.

ANSI IP-67 Dustproof / Waterproof with a 2 meter drop rating.

Includes a heavy-duty rubber, and a nylon head strap **for use on a hard hat.**

CERTIFIED

CE | IECEx | Ex | c UL us LISTED | INMETRO

160 LUMENS

1-800-233-2155 · 1-469-326-9400 · nightstick.com

© 2022 Bayco Products Inc. Items shown are intended as a visual representation for informational purposes only and are subject to change without notice. Visit nightstick.com for product updates.

INTRINSICALLY SAFE

PRODUCT SPECIFICATION SHEET

DUAL-FUNCTION HEADLAMP

RECHARGEABLE

FL1 STANDARD	SPOT HIGH	SPOT LOW	DUAL-LIGHT
	130 LUMENS	70 LUMENS	160 LUMENS
	7h 30min	16h	4h 30min
	87m	UP TO 16 HOURS OF RUNTIME IN LOW MODE	
	1887cd		
2m			
1m			

Segurança
INMETRO OCP 0034
Ex ia IIC T4 Ga
(-20ºC ≤ Tamb ≤ +40ºC)
NCC 21.0077

Bayco Products, Inc. XPR-5554G
640 S. Sanden Blvd., Wylie, TX 75098
Ex ia FLASHLIGHT FOR USE IN HAZARDOUS LOCATIONS
For use with Bayco Li-ion Battery Pack 5554-BATT

c UL us LISTED
E 467756
ID 4003544
INTRINSICALLY SAFE
SECURITE INTRINSEQUE

UK CA 0359 CE 2575

SEE INSTRUCTION MANUAL
VOIR MANUEL
ATENÇÃO – VER MANUAL DE INSTRUÇÕES

CLASS I DIV 1 GRPS A-D T4
CLASS II & III DIV 1 GRPS E-G T135ºC
CLASS I ZONE 0 AEx ia IIC T4 Ga
Ex II 1 G Ex ia IIC T4 Ga
Ex ia IIC T4 Ga
UL 20 ATEX 2400
UL22UKEX2431
IECEx UL 20.0080
-20ºC ≤ Tamb ≤ +40ºC
3.7V/Cell 5554-BATT
Um 4.2V

MFG MM-YY

CERTIFIED
CE IECEx Ex c UL us LISTED INMETRO

ITEM NUMBER/UPC
- XPR-5554G, UPC 0 17398 80788 3

MARKET APPLICATIONS
- Hazardous work environments, industrial, fire & rescue

CERTIFICATIONS
- cULus, CE, ATEX, IECEx, InMetro

CASE MATERIAL
- Engineered Polymer

SPOTLIGHT LUMENS/RUNTIME
- HIGH: 130L, 7.5 hrs. runtime
- LOW: 70L, 16 hrs. runtime

FLOODLIGHT LUMENS/RUNTIME
- HIGH: 130L, 6.5 hrs. runtime
- LOW: 70L, 12.5 hrs. runtime

DUAL-LIGHT LUMENS/RUNTIME
- 160L, 4.5 hrs. runtime

CANDELA
- HIGH: 1,887

BEAM DISTANCE
- 87m

DUST/WATER RATING
ANSI IP-67 Dustproof / Waterproof

DROP RATING
- 2 meters

DIMENSIONS
- LENGTH: 2.1 in (53 mm)
- WIDTH: 2.6 in (66 mm)
- DEPTH: 1.8 in (46 mm)
- WEIGHT: 3.0 oz (85 g)

BATTERY
- Lithium-Polymer (integrated)

WARRANTY
- Limited lifetime warranty

WHAT'S INCLUDED
- Headlamp
- Lithium-Polymer battery
- Elastic non-slip headband
- Heavy-duty rubber head strap
- Strap Back Plate
- Stainless Steel Clip Back Plate
- NS-HMC9 Mount
- 4' (304 mm) USB Male (Type A) Magnetic Coupler Charge Cord
- Alcohol prep pad
- Instruction manual

© 2022 Bayco Products Inc. Items shown are intended as a visual representation for informational purposes only and are subject to change without notice. Visit nightstick.com for product updates. XPR-5554G-22