



CLIMAX 10 LEATHER WELDING APRON

The Climax 10 leather welding apron is designed and constructed to provide full protection against the risk of flying molten metal and glowing particles produced during welding jobs or similar work.

The apron is made of top-quality materials that are not hazardous for the wearer's health and hygiene.

In addition, the apron is specifically designed to protect the wearer's chest, abdomen and upper legs and the system used to secure the apron ensures a snug fit for practically any user.

Description and Features

The Climax 10 welding apron is manufactured of chrome-tanned cowhide leather (cowhide split) and a The apron has a minimum nominal thickness of 1 mm and a fat content of 12%.

The apron has a truncated conical shape from the top to the waist and rectangular shape from the waist to the knees, with a total length of 90 ± 1 cm and bottom width of 60 ± 1 cm. The apron size makes it possible to cover the chest, abdomen and legs until the knees.

The apron is secured by means of beige polypropylene straps with a nominal width of 20 mm and a thickness of 1.4 mm placed around the wearer's waist and neck. The minimum tensile breaking strength is 250 kg. The strap ends are held by means of zinc-coated steel adjustment buckles that prevent the apron from accidentally coming loose and allow the wearer to adjust the straps for a snug fit.

The apron comes in one size only.

Packaging

Individual plastic bag with blister pack and information leaflet
Case of 50 units of the above.

CE Certification

Standards:	UNE-EN 340: 1994 UNE-EN 470-1: 1995 Directive 89/686/CEE
Regulatory agency no.	0159
Certificate no.	41227699

Applications

The Climax 10 apron is ideal for providing full protection against the risk of flying molten metal or glowing particles produced during welding jobs or other work with comparable risks. The apron prevents flame propagation in case of accidental contact with flame.

Technical Data

• Fat content	12%
• pH	3.96 ± 0.02
• Tensile strength	335 N
• Tear resistance	165 ± 0.07 N
• Flame propagation	No propagation
• Molten metal splash resistance	> 40 drops