

EU-Type Examination Certificate

No. P5A 078022 0009 Rev. 00

Holder of Certificate: **Productos Climax, S.A.**

C/Llobregat n° 1
08150 Parets del Vallès (BCN)
SPAIN

Product: **PPE against fall from a height**
Retractable Type Fall Arrestor EN 360

Model(s): **CLIMAX 30M-A**

Tested according to: DIN EN 360:2002
RfU PPE-R/11.060:2018

The Certification Body of TÜV SÜD Product Service GmbH confirms that the listed product fulfils the basic requirements with Annex V (Module B) of Regulation (EU) 2016/425 on personal protective equipment according to Article 19 (PPE of category III). This certificate refers only to the submitted sample for testing and certification and on its technical documentation. The validity of this certificate based on an ongoing surveillance in accordance with Module C2 or D of Regulation (EU) 2016/425 by a Notified Body. For details see: www.tuvsud.com/ps-cert

Test report no.: 028-713263055

Valid until: 2025-05-12

Date, 2022-08-01



(Volker Kron)

EU-Type Examination Certificate

No. P5A 078022 0009 Rev. 00

Parameters:

Function principle:	self-retracting steel cable on drum with centrifugal brake;
Dimensions:	l x w x d: 1030mm x 270mm x 130mm; plastic cover;
Fixation:	oval steel ring (l x b: 90mm x 40mm; \varnothing 10mm thick; in the upper area of the riveted inner frame plates)
Cable length:	30m
Cable:	\varnothing 4,8mm galvanized steel cable 7x19; inner end: 1 aluminium alloy ferrule for end loop; outer end: 1 Nylon damping ball, 1 carbon steel spring, 1 steel thimble with 2 aluminium alloy ferrules, 1 energy absorber, 1 stainless steel U-ring and 1 directional connector with swivel
Rope drum:	\varnothing 120mm x 44mm; aluminium;
Centrifugal brake:	4 spring activated steel clamps in steel brake ring; use in steel gear disc
Rewind system:	stainless steel rewind spring (30mm wide; 0,55mm thick; 35m long), POM pad covered
Energy absorber:	tear-off webbing type energy absorber R-SA1 made of 45mm wide orange PES webbing and 45mm wide white PES webbing with open and tear-off construction; folded length: 245mm, folded height: 42mm, in shrink tube and textile bag; attachment ends on webbing stitched with programmed stitching 36,5mm x 35mm (PES yarn), 174 stitches; attachment ends with black abrasion protection cover PES webbing
Swivel connector:	Type S-2146; steel directional connector with swivel EN 362-A/T
Fixation connector:	Type S-507; steel connector EN 362-B
Marking:	Manufacturer, manufacturing address, EU importer, EU-importer address, model, length, wire diameter, CE-marking, EN 360:2002; RfU PPE-R/11.060; "read instructions"-pictogram, serial no., max. working load: 120kg; warning pictograms, production date: MM/YYYY,
Weight:	13854 grams (30m version)

