


TECHNICAL DATA SHEET				
	TDS No:	177	Issue No:	1
	Issue Date:		09/10/18	
	Revision Date:		09/10/20	
	Page No:		1 of 1	
PRODUCT		Photoluminescent Aluminium Stair Nosing Class G		

DESCRIPTION

A Class G Photoluminescent aluminium stair nosing designed to illuminate stairways, during black out situations, to allow occupants to vacate a building safely.

PHYSICAL PROPERTIES	NOMINAL RESULTS
Size	70mm x 22mm x 1000mm
Materials	Aluminium Photoluminescent Pigment
Glow Colour	Yellow-Green
Glow Properties; 10min 60min Decay Time	>600mcd/m ² >90mcd/ m ² >8000min
Fixing Method	Self-Adhesive Tape or Plastic Bulge Tube and Screw
Weight	0.47Kg/m

<https://www.marinelite.gr>

Olympiton 17,
185 41, Piraeus,
Greece
Tel.: +30 210 4534855
Fax: +30 210 4534865
E-mail: info@marinelite.gr

Disclaimer

The information contained herein is produced in good faith and is believed to be reliable but is for guidance only. Marine Lite Printing S.A & its agents cannot assume liability or responsibility for results obtained in the use of its products by persons whose methods are outside or beyond our control. It is the users' responsibility to determine the suitability of any of the products and methods of use or preparation prior to use mentioned in our literature and furthermore the users' responsibility to observe and adopt such precautions as may be advisable for the protection of personnel and property in the handling and use of any of our products.