

CMP SERIES v1.6

SUBMERSIBLE HEAVY DUTY SPEAKER MICROPHONE

Quick Start User Guide



Designed in the United Kingdom

Entel

CMP SERIES

Thank you for purchasing the Entel remote speaker microphone. This user guide will explain the features of your submersible speaker microphone. With care, this product should provide years of trouble free use.

FITTING

Use the revolving clip to attach the speaker microphone to a pocket or collar. The clip may be rotated into one of eight locking positions to aid attachment.

Insert the plug into the transceivers accessory connector and fasten securely. Always disconnect your speaker microphone with care as undue force may damage it.

OPERATING INSTRUCTIONS

- Press the PTT button to transmit and release to receive.
- When transmitting, talk slowly and clearly, holding the microphone about 5cm away from your mouth.
- Care should be taken when holding the speaker to your ear as high volumes are possible.
- Should you expose the speaker microphone to any potentially corrosive substance, including salt water, it is recommended that you rinse the unit in fresh water. After washing, please vigorously shake the unit to dispel water from the speaker grill.

- If you detach the this accessory from the radio, take care to protect the accessory connector by re-fitting the original accessory cover.

IMPORTANT

Always switch the radio off before attaching an audio accessory. Models that are certified to ATEX & IECEx have been clearly labelled. Should, in the course of use, any labels be removed or become illegible please return the accessory to Entel for relabelling.

SPECIFICATIONS

SPEAKER MICROPHONE

Submersible IP67 (1 metre for 30 minutes)

Mic. element	Electret condenser
--------------	--------------------

Speaker impedance	8 ohms
-------------------	--------

Microphone impedance	<680 ohms
----------------------	-----------


Output sound level pressure	80dBA +/- 10dB
-----------------------------	----------------

Rated input	500 mW
-------------	--------

Maximum input	1 W
---------------	-----

Dimensions	75 x 60 x 35mm
------------	----------------

Weight	154g
--------	------



Above approvals apply to specific models only

Model	Series	Intrinsically safe cert. no.	Approval
CMP500	HT500	IECEX SIR 10.0097X	IECEX
CMP750	HT700	None	None
CMP950	HT800, HT900	Sira 10ATEX2066X	ATEX
CMP450	HX	None	None
CMP450/DX	DX, DN	None	None
CMP/DT5	DT500	IECEX BAS 18.0094X	IECEX
CMP/DT9	DT800, DT900	Baseefa18ATEX0152X	ATEX



8320

Contact

For more information about our products please contact us:

☎ **+44 (0)20 8236 0032**

✉ **info@entel.co.uk**

💻 **entel.co.uk**