

CODE: MBK13-060PA-P1LFR (GER)

ERP: 0135495

Knob-operated 6Kg fire Extinguisher Portable

Knob-operated 6Kg fire Extinguisher with one seam vessel. > **Metallic Bracket included**



CHARACTERISTICS

Capacity	6Kg
Extinguishing Agent	ABC 40%
Operating Temperature	-30 μέχρι +60 °C
Max Allowable Pressure	18 bar
Test Pressure	27 bar
Volume of Equipment	7,8 lt
Cylinder Height	455±5 mm
Cylinder Diameter	160±2 mm
Cylinder Neck Thread	M74x2
Cylinder Material	DC01 (St12)
Valve Material	Al6061-T6
Safety Valve	21-26 bar
Approx. gross Weight	9,34 kg
Approx. Dimensions	600x210 mm
Paint Finish	RAL 3000
Packaging Details	1 τμχ.



Issue Date: 22/02/2023

Information may change

HEADQUARTERS: KATHIANA AKROTIRIOU P.C. 73100 CHANIA, CRETE - GREECE, TEL.: +30 28210 63222, FAX: +30 28210 91644

ATHENS DISTRIBUTION CENTER: SHINEZA - ASPROPIRGOS, P.C. 19300, ATTICA - GREECE, TEL.: +30 210 4614006, FAX: +30 210 5595986

NORTH GREECE DISTRIBUTION CENTER: 8 ARKADIOU str. KALOCHORI - THESSALONIKI, P.C. 57009, TEL.: +30 2310 785668, FAX: +30 2310 574793

CENTRAL & EAST CRETE DISTRIBUTION CENTER: P' str. INDUSTRIAL ZONE OF HERAKLION - CRETE - GREECE, P.C. 71601, TEL/ FAX: +30 2810 333151

www.mobiakfire.com