











CODE: MBK09-250PA-H1B

ERP:

0135202

## **Trolley Fire Extinguisher 25Kg Dry Powder**

Trolley

Trolley Fire Extinguisher, 25Kg Dry Powder ABC 40%, with 5m Discharge Hose and Valve with Pressure Gauge Safety Release Mechanism.

SILKSCREENED USAGE-MAINTENANCE INSTRUCTION LABEL

3rd Wheel added on the Front Side of the Fire Extinguisher Carriage for Easier Usage- Handling.



| Characteristics        |                    |
|------------------------|--------------------|
| Capacity               | 25Kg               |
| Fire performance       | A IB C             |
| Extinguishing agent    | ABC 40% Dry Powder |
| Operating temperature  | -30°C to 60°C      |
| Average discharge time | 30.00sec           |
| Test pressure          | 27bar              |
| Max allowable pressure | 18.00bar           |
| Volume of equipment    | 30.00Lt            |
| Cylinder material      | DC03               |
| Cylinder height        | 720 ± 3 mm         |
| Cylinder diameter      | 250 ± 1 mm         |
| Cylinder neck thread   | 30 x 1.5 mm        |
| Valve material         | HPb59-1            |
| Safety valve           | 21-26 bar          |
| Paint Finish           | RAL 3000           |
| Approx. Gross Weight   | 51.00Kg            |
| Approx. Dimensions     | 950 x 570 x 550 mm |
| Packing Details        | Atomic Carton Box  |











HEALTH & SAFETY MANAGEMENT SYSTEM
OHSAS 18001:2007
QA-C-510B/12









