











CODE: MBK09-500PA-H1B

ERP: 0135203

Trolley Fire Extinguisher 50Kg Dry Powder

Trolley

Trolley Fire Extinguisher, 50Kg Dry Powder ABC 40%, with 5m Discharge Hose and Valve with Pressure Gauge Safety Release Mechanism.

SILKSCREENED USAGE-MAINTENANCE INSTRUCTION LABEL

3rd Wheel added on the Front Side of the Fire Extinguisher Carriage for Easier Usage- Handling.



Characteristics	
Capacity	50Kg
Fire performance	A IIIB C
Extinguishing agent	ABC 40% Dry Powder
Operating temperature	-30°C to 60°C
Average discharge time	55.00sec
Test pressure	27bar
Max allowable pressure	18.00bar
Volume of equipment	56.00Lt
Cylinder material	DC03
Cylinder height	900 ± 1 mm
Cylinder diameter	390 ± 2 mm
Cylinder neck thread	30 x 1.5 mm
Valve material	HPb59-1
Safety valve	21-26 bar
Paint Finish	RAL 3000
Approx. Gross Weight	84.00Kg
Approx. Dimensions	1080 x 630 x 565 mm
Work pressure at 20°C	15bar
Approx. Discharge Distance	11m
Packing Details	Atomic Carton Box









HEALTH & SAFETY MANAGEMENT SYSTEM
OHSAS 18001:2007
QA-C-510B/12









