

Product Code: MBK03-500AF-W1B

ERP: 0135033

Trolley Fire Extinguisher 50Lt Foam

Trolley

50Lt Trolley Foam Fire Extinguisher with 5m Discharge Hose. Vessel with Internal Anti-Oxidation Coating. Valve with Pressure Gauge Safety Release Mechanism.



Characteristics

Capacity	50Lt
Fire performance	A IIIB
Extinguishing agent	AFFF 6% Foam
Operating temperature	0°C to 49°C
Average discharge time	143.00sec
Test pressure	27bar
Max allowable pressure	18.00bar
Volume of equipment	59.00Lt
Cylinder material	DC03
Cylinder height	900 ± 3 mm
Cylinder diameter	300 ± 1 mm
Cylinder neck thread	30 x 1.5 mm
Cylinder Thickness	2.50mm
Valve material	HPb59-1
Paint Finish	RAL 3000
Approx. Gross Weight	86.00Kg
Approx. Dimensions	1080 x 630 mm
Packing Details	Atomic Packing

Factory-Product Showroom: Akrotiri, Chania, Crete, P.C.: 73100, Tel: +30 28210 63222, Fax: +30 28210 66260

Central: 96-98 Markou Botsari Str., Chania, Greece, PC: 73136

Distribution Center-Athens: Magoula, Aspropirgos, Attica, P.C.: 19300, Tel: +30 210 4614006, Fax: +30 210 5595986

Distribution Center-N.Greece: 8 Arkadiou Str., Kalochoi, Thessaloniki, P.C.: 57009, Tel: +30 2310 785668, Fax: +30 2310 574793

Distribution Center-Central & Eastern Crete: P' Str., Industrial Zone of Heraklion, Crete, P.C.: 71601, Tel/Fax: +30 2810 333151

Web site: www.mobiak.gr, e-mail: info@mobiak.gr

