

CODE: MBK02-050CA-P1A

ERP: 0135034

Fire Extinguisher 5Kg CO2 EXCLUSIVE Portable

Fire Extinguisher 5Kg Carbon Dioxide with EDPM discharge hose with horn and plastic handle

Height: 760mm

Galvanized bracket included

[FIRE EXTINGUISHERS USER INSTRUCTIONS](#)



CHARACTERISTICS

Approval Type	APRAGAZ, BENOR, CNBOP, ITALY, KIWA, MED, MIRTEC, MPA DRESDEN, NF, TSE, VKF
Extinguisher Type	Portable
Pressure Type	Stored Pressure
Suppression Agent Type	CO2
Capacity	5Kg
Extinguishing Agent	CO2
Operating Temperature	-30 to +60 °C
Max Allowable Pressure	169,3 bar
Test Pressure	250 bar
Volume of Equipment	7,5 lt
Cylinder Height	655±6,55 mm
Cylinder Diameter	138 ± 1,38 mm
Cylinder Neck Thread	25E
Valve Material	HPb59-1 (Nickel Plated)
Cylinder Material	34CrMo4
Safety Valve	225±25 bar
Approx. gross Weight	14,5 kg
Approx. Dimensions	750 x 200 mm
Paint Finish	RAL 3000
Packaging Details	1 pc.



ATHENS DISTRIBUTION CENTER: SHINEZA - ASPROPIRGOS, P.C. 19300, ATTICA - GREECE, TEL.: +30 210 4614006, FAX: +30 210 5595986

NORTH GREECE DISTRIBUTION CENTER: 8 ARKADIOU str. KALOCHORI - THESSALONIKI, P.C. 57009, TEL.: +30 2310 785668, FAX: +30 2310 574793

CENTRAL & EAST CRETE DISTRIBUTION CENTER: P' str. INDUSTRIAL ZONE OF HERAKLION - CRETE - GREECE, P.C. 71601, TEL/ FAX: +30 2810 333151

www.mobiakfire.com