

CODE: MBK06-100CA-P1A

ERP: 0129000

Trolley Fire Extinguisher 10Kg CO2 Trolley

10Kg CO2 Trolley Fire Extinguisher with 16Lt Cylinder with 5m Discharge Hose.

HIGH-PRESSURE EPDM Discharge Hose of WP 155bar with Plastic Handle and Flow Control Valve, according to EN853 requirements, HEAVY Duty Carriage and wheels, Valve Protection HANDLE

[FIRE EXTINGUISHERS USER INSTRUCTIONS](#)



CHARACTERISTICS

Approval Type	MED, MIRTEC
Extinguisher Type	Trolley
Pressure Type	Stored Pressure
Suppression Agent Type	CO2
Capacity	10Kg
Extinguishing Agent	CO2
Operating Temperature	-20 to +60 °C
Max Allowable Pressure	174 bar
Test Pressure	300 bar
Volume of Equipment	16 L
Cylinder Height	685±6,85 mm
Cylinder Diameter	200±2 mm
Cylinder Neck Thread	25E
Valve Material	DC01 (St12)
Cylinder Material	HPb59-1 (Nickel Plated)
Safety Valve	250-275 bar
Approx. gross Weight	63,8 kg
Approx. Dimensions	1100x400 mm
Paint Finish	RAL 3000
Packaging Details	1 pc.

EN1866



2010/35/EU (IT)

EN1964

Issue Date: 23/05/2024

Information may change

HEADQUARTERS: KATHIANA AKROTIRIOU P.C. 73100 CHANIA, CRETE - GREECE, TEL.: +30 28210 63222, FAX :+30 28210 91644

ATHENS DISTRIBUTION CENTER: SHINEZA - ASPROPIRGOS, P.C. 19300, ATTICA - GREECE, TEL.: +30 210 4614006, FAX: +30 210 5595986

NORTH GREECE DISTRIBUTION CENTER: 8 ARKADIOU str. KALOCHORI - THESSALONIKI, P.C. 57009, TEL.: +30 2310 785668, FAX: +30 2310 574793

CENTRAL & EAST CRETE DISTRIBUTION CENTER: P' str. INDUSTRIAL ZONE OF HERAKLION - CRETE - GREECE, P.C. 71601, TEL/ FAX: +30 2810 333151

www.mobiakfire.com