

CODE: MBK19-LITHIUM-2

ERP: 0501127

Portable Fire Extinguisher 2Lt for Lithium Batteries Foam - Water

Fire Extinguisher 2Lt Water with complement, with One Seam Vessel with INTERNAL PLASTIC LAYER and External thread, Pressure Gauge Safety Release Valve and Gauge non return Valve. Appropriate for use at Lithium Batteries Fires. Metallic Bracket Included.



CHARACTERISTICS

Capacity	2
Extinguishing Agent	Water with complement
Operating Temperature	+5°C ~ +60°C °C
Max Allowable Pressure	20 bar
Test Pressure	30 bar
Volume of Equipment	3,2 lt
Cylinder Height	304±2 mm
Cylinder Diameter	130±2 mm
Cylinder Neck Thread	M45x1.5
Valve Material	DC04/DC03
Cylinder Material	AA6061 (anodized)
Safety Valve	22~27 bar
Approx. gross Weight	~4 kg
Approx. Dimensions	410x160 mm
Paint Finish	RAL3000
Packaging Details	1 pcs.

BENOR



CE

Issue Date: 26/09/2021

Information may change

FACTORY: AKROTIRI, CHANIA, P.C. 73100, TEL. +30 2821063222, FAX: +30 28210 66260

CENTRAL EXHIBITION: 96-98 M. MPOTSARI str. P.C. 73136, CHANIA, GREECE, TEL. +30 28210 91561, FAX +30 28210 91644

ATHENS DISTRIBUTION CENTER: SXINEZA- ASPROPIRGOS, P.C. 19300, TEL. +30 210 4614006, FAX +30 210 5595986

N.GREECE DISTRIB. CENTER: 8 ARKADIOU str. KALOCHORI - THESSALONIKI, P.C. 57009, TEL. +30 2310 785668, FAX +30 2310 574793

CENT. & EAST CRETE DISTRIB. CENTER: P' str. INDUSTRIAL ZONE OF HERAKLION - CRETE, P.C. 71601, TEL./FAX +30 2810 333151

www.mobiakfire.com