

FG9-F XF

Cartridge
operated

Fluorine Free

9 Lt

Temperature ranges

+5° + 60°



27



183

BODY

STEEL

3-pieces mild steel cylinder, wire feed welded, with internal PE coating. Externally painted with polyester resin.

VALVE

ALUMINUM

Lever operated valve with anodized aluminum body, ensuring high protection against corrosion.

EXTINGUISHING AGENT

Water with additives (to improve class A) and FLUORINE FREE. All parts in contact with the extinguishing agent are compatible.

PROPELLANT

Rechargeable CO2 cartridge, deep drawn without welds, externally protected by zinc coating and passivation. Plastic coated.

HOSE/HORN

The EPDM reinforced rubber hose guarantees perfect flexibility and resistance within the temperature range. Complete with nozzle.

PACKAGING

Single piece cardboard box, robust and suitable for transport.



Configuration

● Standard

○ On request

BRACKET



○ Button holed wall bracket PG-M E FG-M



○ TRANSPORT BRACKET PG9-F

PACKAGING



○ BOX PG9-F


HOSE RINGS & PROTECTIVE
BASE



○ PROTECTIVE BASE Ø160 GREEN

Technical data

FIRE RATINGS	27A 183B	
CHARGE	9 Lt 0 / -5%	
MATERIAL	STEEL	
CYLINDER	Manufacturing process	Calandering Welding
	External painting	Polyester Resin
	Corrosion resistance	480 H SECONDO ISO 9227:2017
EXTINGUISHING AGENT	WATER WITH ADDITIVES	
PROPELLANT	CO2	
DISCHARGE	Discharge time	~ 87 s
DIMENSIONS	Overall height	820 mm
	Bottle outer diameter	160 mm
	Empty / Charged	5.48 kg / 14.75 kg
PACKING SPECIFICATIONS	Standard packing	1 Pieces cardboard box
	Carton size (B x L x H)	175 x 230 x 775 mm
	Weight per carton	15.36 kg
	Pallet	42 Cartons
	Pallet size (B x L x H)	800 x 1200 x 1510 mm
	Pallet volume	1.45 m3
	Weight per pallet (net/gross)	645 kg / 665 kg



Spare parts list

Description	Code
WALL BRACKET	00.005E.2950.00K0
BURSTING DISC	00.040E.2400.ALK0
MANICHETTA FG-M FFX COMPLETA	00.041E.2400.10K0
CO2 DIP TUBE	00.041E.5951.00K0
GASKET	00.050E.5000.ORK0
SPINDLE	00.050E.5035.00K0
PULSANTE PG-F SAGOMATO STAMP. VERDE	00.050E.6000.10K0
TRANSPORT BRACKET	00.050F.2900.00K0
DIP TUBE	00.050F.5900.00K0
VALVE ASSEMBLY WITH BLUE LEVEL	00.051E.8490.90K0
60G CO2 CARTRIDGE	00.051F.3900.01K0
Valve assembly	00.051F.8500.00
White SEAL	00.245E.5030.00K0
SAFETY PIN	00.580E.5020.00K0
Base Ø160	00.890E.7100.10
DADO ESAGONALE CIECO M8; RICAMBI	N000.VT.050.00K0

ANAF Fire Protection

Via del Commercio, 4 - Torre d'Isola (Pavia) - Tel. 0382.4533 Fax. 0382.920279
info@anaf.eu | www.anaf.eu