

CODE: MBK24-1350FF-EXT

ERP: 0135910

Trolley Fire Extinguisher 135Lt Fluorine Free Foam Fluorine Free

Trolley Fire Extinguisher, 135Lt, with 5m Discharge Hose The external cartridge contains Nitrogen (N2) as propellant gas

[FIRE EXTINGUISHERS USER INSTRUCTIONS](#)



CHARACTERISTICS

Approval Type	MED, MIRTEC
Extinguisher Type	Fluor Free, Trolley
Pressure Type	Cartridge
Suppression Agent Type	Foam
Capacity	135Lt
Extinguishing Agent	water + 2% MBK LIQ WLD + 5% MBK LIQ FFA
Operating Temperature	+5~+60 °C
Max Allowable Pressure	20 bar
Test Pressure	30 bar
Volume of Equipment	147 L
Cylinder Height	1295±4 mm
Cylinder Diameter	407±1 mm
Cylinder Neck Thread	M74x2
Cylinder Material	HP295
Valve Material	CuZn40Pb2
Safety Valve	22-27 bar
Approx. Dimensions	1700x600 mm
Paint Finish	RAL 3000
Packaging Details	1 pc.



EN1866



Issue Date: 10/02/2026

Information may change

HEADQUARTERS: KATHIANA AKROTIRIOU P.C. 73100 CHANIA, CRETE - GREECE, TEL.: +30 28210 63222, FAX :+30 28210 91644
ATHENS DISTRIBUTION CENTER: SHINEZA - ASPROPIRGOS, P.C. 19300, ATTICA - GREECE, TEL.: +30 210 4614006, FAX: +30 210 5595986
NORTH GREECE DISTRIBUTION CENTER: 8 ARKADIOU str. KALOCHORI - THESSALONIKI, P.C. 57009, TEL.: +30 2310 785668, FAX: +30 2310 574793
CENTRAL & EAST CRETE DISTRIBUTION CENTER: P' str. INDUSTRIAL ZONE OF HERAKLION - CRETE - GREECE, P.C. 71601, TEL/ FAX: +30 2810 333151
www.mobiakfire.com