




HI-RISE 275N SOLAS LIFEJACKET AUTO HARNESS MODEL NO. 2MS1



GENERAL

- Approved to new 2010 SOLAS regulations (according to MSC.200(80) and MSC.207(81))
- Offers much higher performance levels in water for freeboard (height of mouth from water level): face plane angle (uplift of head from water level) : body angle (higher flotation angle in water)
- One size now fits all adults between 40kgs and 120 kgs or more/ between less than 1.5m height and above 1.9m height/ up to a 1.75m chest girth
- A floating buddy line is now fitted as standard to all SOLAS lifejackets



DESIGN

- A standard horseshoe design of lifejacket of comfortable design with offset shoulder straps to alleviate weight and pressure stress on neck and shoulders
- New 3D cover with gusset feature for ergonomic comfort and alleviation of bulk
- Double zip fastening cover using YKK special lifejacket zips with corrosion proof Teflon sliders. Burst point facilitating bladder inflation is at the opening between the 2 zips at the centre back neck. Back neck burst point is secured for working use with Velcro
- 50mm Mullion logo polypropylene red/ black webbing adjustable waist belt with loose end of webbing secured by a 50mm nylon acetal retainer and fastened at centre front by means of high strength marine grade stainless steel interlocking buckles
- High strength marine grade stainless steel D-Ring fitted to centre front waist belt for attachment of safety line



INFLATION MECHANISM OPTIONS

2MS1A2N06: Hammar MI/AI standard hydrostatic auto

2MS1A3N06: United Moulders Mark 5 standard auto

2MS1A4N06: Halkey Roberts Alpha standard auto

Colours: Navy/Black (353)

Red/Black (412)



OUTER COVER

- Cover in durable 450 denier polyurethane polyester – duo-colours – red black or navy / black
- Reflective silver piping feature applied vertically to the fronts
- 50mm black polypropylene webbing harness and shoulder straps
- 1 x 25mm black polypropylene webbing adjustable central crutch straps fitted to back strap at rear and fitted at front with clip in 25mm nylon acetal side release attachment buckles. A 25mm nylon acetal retainer is fitted to secure loose end of webbing
- 25mm red polypropylene webbing grab / lifting strap fitted to inside of cover + LIFT lettering incorporated for clear identification of use

BLADDER & MECHANISM

- 275N twin chamber bladder - colour Spanish yellow
- Unique hinged head pillow for optimum comfort and head support in-water
- Unique moulded shape tailored to the contours of the wearer for comfort and snug secure fit
- 2 automatic inflation systems fitted– 1 front / 1 back
- 60gram Co2 gas cylinders fitted to inflation mechanisms
- 50mm marine grade SOLAS approved kiss - cut reflective tape applied to bladder.
- Over pressure oral tube + relief valve on front chamber for manual inflation and deflation and also to relieve any excess pressure if both chambers are fired simultaneously
- Marine grade ISO 12402 approved clip-on orange whistle attached to cord in elastic holder on front oral tube for easy location
- Standard Oral tube for manual inflation and deflation on back chamber
- Lifting loop handle secured to bladder by Velcro to ensure ease of location and access
- Floating high-visibility orange buddy line + easy-grip toggle attached in elastic holder on right front edge of bladder – for enhanced security to attach to “buddies” in-water
- Solas UML SOS flashing light water evacuation+ manual function attached to the bladder



Unique moulded shape tailored to the contours of the wearer for comfort.



Marine grade ISO 12402 approved clip-on orange.



Lifting loop handle secured to bladder by Velcro.



A floating buddy line

MULLION UK

44 NORTH FARM ROAD
SOUTH PARK INDUSTRIAL ESTATE
UK-SCUNTHORPE NORTH LINCOLNSHIRE DN17 2AY
TEL.: +44 (0) 1724 280077
FAX: +44 (0) 1724 280146
SALES_UK@MULLIONMANUFACTURING.COM

WWW.SIDEN.COM

MULLION EXPORT OFFICE

FABRIEKSTRAAT 23
B-8850 ARDOOIE
BELGIUM
TEL.: +32 (0) 51 741 502
FAX: +32 (0) 51 740 963
KURT.SMITS@SIDEN.BE

WWW.MULLION.BE

