



TECHNICAL DATA SHEET

Lifejacket Lights

M3, MR3, ML3, W3, WR3 & WL3

Daniamant design and manufacture all of our products in line with the Quality Management System (ISO), relevant worldwide approvals, technical specifications, current legislation and International directives.

Our mission is to achieve World class performance through partnerships with our suppliers, customers and employees, providing products and services that enhance the safety and security of our customers.

Daniamant products cover five key areas:

- Lifejacket Lights
- Liferaft Lights
- Lifebuoy Lights
- Intrinsically Safe Lights
- Special Lights

Further Information

The Product Brochure, Installation & Operating Instructions & Product Safety Data Sheet (PSDS) can all be found on our web site. This information was correct at time of going to press, please check our web site for any updates.

Daniamant operates a policy of continuous improvement and reserves the right to amend the specifications in accordance with that philosophy.

MODEL	M3	MR3	ML3	W3	WR3	WL3
Part number	1130	1230	-	1330	1430	-
Colour - Light	Blue (Standard)					
Light - Output	Minimum 0.75 cd					
Light - Duration	Minimum 8 hours					
Light - Type	Flashing LED					
Material	ABS Polycarbonate/TPE					
Storage Temperature	-30°C to +65°C					
Operating Temperature	-1°C to +30°C					
Storage Life	5 years					
Weight - Nominal	35 g	31 g	42 g	35 g	31 g	42 g
Battery Type	Lithium Manganese Dioxide					
Activation	Manual			Water/Manual		
Approvals - Classification Societies	SOLAS/MED/USCG					
Approvals - Country	See our web site for full list of Country approvals					

Transport Specification

UN Hazard Code: Exempt from transport packing, marking and labelling regulations under surface ADR & IMDG Special Provision 188, IATA Packing Instruction 970 Section II

UN Number: 3091

UN Proper

Shipping Name: Lithium metal batteries contained in equipment

Packing Group: II

Lithium Content
All types: 1 cell (0.54 g)

Watt hour rating
All types: 4.65 wh

Labelling: Packages must be labelled with the Lithium Battery Handling label

Packing Specification

To minimize shipping costs, all Lifejacket Lights are packed and supplied in boxes of 250 and 500 off.

The dimensions are:

Box of 250 off: 40 x 40 x 24 cm
Box of 500 off: 78 x 40 x 24 cm

Approximate packed weights are:

Box of 250 off: 14 kg
Box of 500 off: 23 kg

Daniamant ApS

Industrivej 24C
3550 Slangerup
Denmark

Tel +45 47 37 38 00
Fax +45 47 37 38 09
orders@daniamant.com

Daniamant Ltd

Unit 3, The Admiral Park
Airport Service Road
Portsmouth, PO3 5RQ
United Kingdom

Tel +44 23 92 67 51 00
Fax +44 23 92 67 51 01
sales@daniamant.com

